JOHNSTONE SUPPLY

N-2636 June 27, 2012

# NEW PRODUCTS NOW AVAILABLE AT JOHNSTONE SUPPLY CATALOG #204 AND WEB

## NEW PRODUCTS: RECOVERY UNIT, SCALES, AND WRENCH SETS FROM cps

### PRO-SET® TR21 Recovery Unit

- Maintenance free 2-cylinder oil-less reciprocating compressor
- 550 PSI high pressure cutoff switch with LED indicator
- Permanently lubricated and sealed main bearings
- Compact design
- For use with all common refrigerants including R410A
- Precision machined from aluminum and steel components
- One-year warranty

| ORDER# | MFG# | VAPOR REC. RATE - R22 | LIQUID REC. RATE - R22 | PUSH/PULL RATE R22 | WIDTH | HEIGHT | DEPTH | WT. LBS. | LIST EACH |
|---|---|---|---|---|---|---|---|---|---|
| H85-665 | TR21 | 0.597 | 8.86 | 31.53 | 6" | 9" | 12" | 24.5 | $1,645.00 |

### PRO-SET® MT69 Molecular Transformator

- Increase performance of any recovery machine
- Cuts recovery time in half
- Functions as submersible condenser or evaporator
- Transforms hot refrigerant gas molecules into refrigerant liquid molecules
- Transforms cold refrigerant liquid molecules into a warm refrigerant gas
- Maintenance free
- Rugged, compact and easy to use

| ORDER# | MFG# | WIDTH | HEIGHT | DEPTH | WT. LBS. | LIST EACH |
|---|---|---|---|---|---|---|
| H27-417 | MT69 | 4" | 12" | 4" | 5 | $305.00 |

**Compute-A-Charge® Electronic Refrigerant Scales**

- High contrast wide angle LCD Display for ease of viewing
- Platform can be removed from carrying case
- Magnetic back on handheld unit
- Hanging hook
- User selectable automatic power off to conserve batteries.
- Designed and manufactured in our factory in Hialeah, Fl. USA
- Accuracy: 0.05% of reading or ± 0.2oz / (± 5g) whichever is greater

**CC110 Specifications:**

- 110 lbs. (50kg) capacity
- 8.75" x 8.75” removable platform
- Power: Two AA batteries, included

**CC240RF Specifications:**

- RF Wireless
- Advanced communication software ensures uninterrupted connectivity between hand-held display unit and scale platform
- 240 lbs. (110kg) capacity
- 8.75" x 8.75” removable platform
- Power: Four AA (scale platform); one 9V battery (display unit); all included

**CC840RF Specifications:**

- RF Wireless
- User programmable, fully automatic operation
- Advanced communication software ensures uninterrupted connectivity between hand-held display unit and scale platform
- 240 lbs. (110kg) capacity
- 10" x 10” removable platform
- Power: Four AA (scale platform); one 9V battery (display unit); all included

| ORDER# | MFG# | DESCRIPTION | LIST EACH |
|---|---|---|---|
| H27-418 | CC110 | CHARGING/RECOVERY SCALE | $379.00 |
| H85-666 | CC240RF | WIRELESS CHARGING/RECOVERY SCALE | 519.00 |
| H85-667 | CC840RF | WIRELESS CHARGING/RECOVERY SCALE WITH AUTOMATIC PROGRAMMABLE CHARGING | 865.00 |

**PRO-SET® SAE Torque Wrench Set**

- Interchangeable jaw torque wrench provides consistent and accurate readings
- Use to ensure compliance with OEM torque settings on R410A mini-split systems
- Range of 0 to 80 ft/lb. torque
- Includes storage case with 5/8”, 11/16”,13/16”, 15/16”, 1-1/16”, and 1-5/16” jaw sizes

| ORDER# | MFG# | DESCRIPTION | LIST EACH |
|---|---|---|---|
| H27-419 | TLTWSAE | SAE TORQUE WRENCH SET | $159.00 |

**R410A Universal A/C Tool and Adapter Kit**

- Includes critical tools needed to properly install & service R410A mini-split systems
- 2-valve, triple seal manifold for R410A
- 5' hose set with ball valves
- Interchangeable jaw torque wrench for 5/8”, 11/16”, 13/16”, 15/16”, 1-1/16”, 1-5/16” flare nuts - 80 ft/lb. range
- Eccentric mandrel R410A flaring tool for 3/16”, ¼”, 5/16”, 3/8”, 1/2”, 5/8” and 3/4” line-sets
- Standard hex key set for 3/32”, 7/64”, 1/8”, 9/64”, 5/32”, 3/16”, 5/32” and 1/4"
- Metric hex key set for 1.5, 2, 2.5, 3, 4, 5, 6 and 8mm
- Brass adapters (5/16" female x 1/4" SAE male) - (2) 55° and (2) straight
- Valve core removal tool (5/16” flare)
- 5/16” R410A brass caps (10)
- Tool bag

| ORDER# | MFG# | LIST EACH |
|---|---|---|
| H85-668 | TLB410SAE | $705.00 |

**Clutch Driven Flaring Tool**

- Flaring tool with ratchet for 3/16", 1/4", 5/16", 3/8", 1/2", 5/8" & 3/4" O.D. tubing
- Engineered to create stronger flare joints for high pressure R-410A systems
- Unique clutch driven feed screw and faceted cone produce uniform, clean flare walls without thin spots or galling
- Provides an exact amount of flaring torque with break-away clutch system

- Innovative 3⁄8" square drive incorporated directly in yoke handle for use of ratchet
- Rugged polyethylene storage case included

| ORDER# | MFG# | LIST EACH |
|---|---|---|
| H85-669 | FT800FN | $215.00 |